

Chutes Enterprises

APARTMENT COMPACTOR

CE-CP Container packer

Specifications

Rating.....0.31 cu. Yds
 Charging area.....24"L x 30.5"
 Top opening.....31"W x 71"L
 Overall dimensions.....31"W x 75"L x 70"H
 Ram dimension.....30.5" x 20"
 Weight.....1600 LBS

Performance

Cycle time.....32.4 secs
 Displacement per hour.....34.4 cu.yds
 Ram penetration.....8 inches
 Ram face pressure(N) @ 1200PSI... 19 psi
 Ram face pressure(M) @ 3000PSI...47psi

Structural

Body sides.....1/4" plate
 Bottom plate.....double layer 1/4" plate with AR400
 Hopper.....11 gauge
 Hopper striker plate.....1/4" plate
 Ram face.....1/2" plate

Electrical

Power unit.....44" x 18" x 16"
 Motor.....3hp, 5hp optional
 Motor power.....208/230/460v 3PH 20A
 Control voltage.....120V
 Controller.....Lovato programmable controller
 Monitors.....Full/Fault and internal HMI
 Photo electric eye.....Pepperl+Fuchs RLK61
 Door safety switch.....Lovato
 Electrical components are UL,IEC/EC & CSA compliant

Hydraulics

Cylinder.....3.5" bore, 1.5" rod
 Pump.....2 stage 11GPM gear pump
 Oil tank.....12 gallons
 Operating pressure.....500 – 1500 PSI
 Relief pressure.....1500 PSI
 Rated pressure.....3000 PSI

